

Mario Bellini

Pendant, ceiling/wall and floor lamps. in natural opal polyethylene, in rotational printing. The floor version is also outdoor. Diffused lighting for a widespread and comfortable output. The pendant version is fastened to the ceiling with three suspension cables, adjustable with an outline included in the package. White canopy freely adjustable on the ceiling. The ceiling/wall version is composed by one of the two blocs (deep or flat, to choose) while the IP44 outdoor version has adjustable feet with possibility of ground fixing. All versions are dimmable. For the pendant version, DALI driver on request.



www.nemolighting.com Page 1



Mario Bellini

LED H20

Lamping

Source LED

Total power 80W

Emission diffused

 Switching
 dimmable 1-10V

 Tension
 110/240V

 Color temperature
 3000K

Luminous flux7900lmTyp cri80Energy classA+

Materials polyethylene


Codes

Structure

Diffuser

NUV LWW 31 white

- -



154

| 20 |

37 I

Package 1

Dimensions93x150x65Gross weight19 Kg

www.nemolighting.com Page 2



Mario Bellini

LED H37

Lamping

Source LED

Total power 80W

Emission diffused

Switching dimmable 1-10V
Tension 110/240V
Color temperature 3000K

Luminous flux 7900lm

Typ cri 80

Energy class A+

Materials polyethylene


Codes

Structure

Diffuser

NUV LWW 32

white



Package 1

Dimensions93x150x65Gross weight19 Kg

154

www.nemolighting.com Page 3